



punjenje ispod trave: mješavina
70% tla i 30% pijeska
grass infill: organic topsoil 70%
and sharp sand 30% mixed

agregatno punjenje: bilo koja
vrsta max. do \varnothing 20mm
gravel infill: any type of gravel up
to \varnothing 20mm

KAKO INSTALIRATI HOW TO LAY GRIDS


izravnavajući sloj 4 cm, pijesak ili šljunak 2-5 mm,
mehanički zbijen
levelling/bedding layer 4 cm of fine stone 2-5mm or
sharp sand well compacted

geotekstil optimalno propušta tip 100-300 g / m²
permeable geotextile 100-300 g/m² recommended

propusni nosivi sloj 20-40 cm po mogućnosti
prirodni drobljeni agregat 0-31,5 mm snažno
mehanički zbijen
sub-base/drainage stone layer 20-40 cm natural
gravel of mixed rock origin 0-31.5 mm fully
compacted

optimalno propusni geotekstil, po potrebi tip 100-300g / m²
permeable geotextile 100-300 g/m² if required

izvorno tlo nakon uklanjanja sloja s nagibom od
1-1,5% u smjeru najboljeg oticanja
soil layer excavated 1-1.5%, falling to a good
drainage point



www.installation.info.pl

